



# Quest Dry RDS 10

## Refrigerant Drying System

### RDS 10 Specifications

<b>Part No.</b>	4029630
<b>Power</b>	5.1 amps, 110V, Grounded
<b>Water Removal</b>	10 Gallons/day @ 80 °F/60%RH 20 Gallons/day maximum @ saturation
<b>Blower</b>	230 CFM
<b>Operating Range</b>	33 °F to 105 °F
<b>Filters</b>	12" x 12" x 1" Pleated Media MERV-11
<b>Duct Options</b>	Inlet - 12" Flex-Duct Outlet - 10" Lay-Flat
<b>Warranty</b>	Five years; 1st year 100% of Parts and Labor 2nd-5th year 100% of Parts of sealed refrigeration system.

### Dimensions

	<b>Machine</b>	<b>Shipping</b>
Width	20"	24"
Height	33.5"	45.25"
Depth	20"	25.5"
Weight	105 lbs	110 lbs

### Accessories and Replacement Filters

4025568	12" x 12" x 1" Pleated Media MERV-11
4026315	12" x 12" x 1" Pleated Media MERV-8
4029252	10" x 250' Lay-flat Duct
4024750	12" x 25' Flex Duct



Quest Dry RDS 10

### Features:

- Lightweight and Portable - 105 lbs
- High Capacity - Up to 20 gallons at saturation
- Energy Efficiency - Draws only 5.1 amps
- Extended Operating Range - 33 °F to 105 °F
- Process Airflow - 230 CFM
- Durable, Plastic Housing - Resists dents and scratches
- Retractable Handle - A heavy-duty retractable handle for easy storage, transporting and stacking multiple units
- Recessed 12" Wheels - Allows greater maneuverability on the job site and efficient storage. Rolls over obstacles with ease
- Pleated Air Filter
- Inlet Ducting - 12" Flex Duct
- Outlet Ducting - 10" Lay-Flat
- Solid State Controls - Easy to read and operate
- Internal Condensate Pump - Removes water that collects in the reservoir
- Protected Condensate Hose - Recessed hose cannot catch or be damaged on obstructions



Engineered Excellence for Construction Professionals



Specifications subject to change without notice. 03/17



Therma-Stor<sup>®</sup> LLC  
4201 Lien Rd  
Madison, WI 53704

1-866-933-7486  
www.QuestOnTheJob.com