



Quest PowerDry 1200D Pro

Desiccant Dehumidifier

PowerDry 1200D Pro Specifications

Part Number	4028200
Power	220V single phase unit One cord (19' – un-terminated): User selectable 25 or 40 amp draw
Water Removal	344 pints/day (43 Gallons) @ AHAM (80°F, 60%)
Blower	900 CFM Process Airflow 300 CFM React Airflow
Operating Range	-10°F to 140°F
Duct	Process/React oval inlet: 12" flex duct (optional)
Options	Process Outlet: 8" flex duct or layflat Reactivation Outlet: 8" flex duct (required)
Warranty	Two years; 1st year Parts and Service 2nd year Silica Gel Rotor
Dimensions	Machine
Width	26.5"
Height	35"
Depth	45"
Weight	265 lbs
Accessories	
4029521	Flex Duct 12"x25'
4029252	Lay Flat Duct 10" Round x 250'



Quest PowerDry 1200D Pro

Features:

- 900 CFM process airflow
- 300 CFM reactivation airflow
- 12" Oval inlet
- 8" Reactivation Outlet
- Dual 8" Process Outlets
- 220V single phase:
 - User selectable 25 or 40 amp draw
 - All the standard 120 volt outlets available for Quest air movers
- 344 pints (43 gallons) per day @ AHAM
- Fits easily through doors, up truck ramps and in SUVs
- Quiet operation
 - Constant run mode or humidistat controlled mode
- Hi-Lo handles for easy lifting
- External filter for simple maintenance
- Tough weather resistant design
- Operating Range -10°F to 140°F



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 03/17



Therma-Stor^{LLC}
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com