

Quest PowerDry 4000 Pro



Refrigerant Dehumidifier

PowerDry 4000 Pro Specifications

Part No.	4031160
Power	10 amps, 110V, Grounded
Water	22 Gallons/day @ AHAM (80 °F, 60%) 36 Gallons/day maximum @ saturation
Removal	
Blower	380 CFM without external ducting
Refrigerant	2 lbs, 2 oz. R-410A
Charge	
Operating Range	33 °F to 105 °F
Filters	15.5" x 19.5" x 1.75" Pleated Media MERV-11
Duct Options	Inlet – 12" Flex-Duct Outlet – 10" Lay-Flat
Warranty	Five years; 1st year 100% of Parts and Labor 2nd-5th year 100% of sealed refrigeration system parts.

Dimensions

	Unit	Shipping
Width	20"	24"
Height	40"	47"
Depth	23"	26"
Weight	135 lbs	148 lbs

Popular Accessories And Replacement Filters

4024750	12" x 25' Intake Flex Duct
4029252	10" x 250' Lay-flat Duct
4024969	16" x 20" x 2" Pleated Media MERV-8
4021475	16" x 20" x 2" Pleated Media MERV-11 (Standard)
4030115	Reed LM-8000 Meter



Quest PowerDry
4000 Pro

ETL Listed



Features:

- High capacity – 176 pints/day @ AHAM (22 Gallons)
- Onboard humidistat for continuous humidity control
- High energy efficiency – Requires only 10 Amps of electricity
- Pleated media filter – Standard MERV 11 filtration reduces dust
- Multiple Ducting Options - 12" inlet, 10" outlet.
- Reservoir pump system – Strong and dependable, 20 ft of lift
- Solid State Controls - Easy to read and operate
- Digital hour meter – Easy to read for more accurate billing
- 25-ft power cord – No need for extension cords
- 30-ft drain hose – Pump condensate to sinks or drains



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 03/17



Therma-Stor LLC
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com