



# Quest PowerDry 4800D Pro

## Desiccant Dehumidifier

### PowerDry 4800D Pro E (Electric) Specifications

<b>Part No.</b>	4028203 (with Frame) 4029193 (without Frame)
<b>Power</b>	480V three-phase unit, 106 amps
<b>Water</b>	3032 pints/day @ AHAM
<b>Removal</b>	(379 Gallons)
<b>Blower</b>	4800 CFM Process Air
<b>Operating Range</b>	-10°F to 140°F
<b>Duct Options</b>	18" to 20" Flex Duct and Lay Flat
<b>Warranty</b>	2 years; 1st year Parts and Service 2nd year Silica Gel Rotor

#### Dimensions

Width	48"
Height	56"
Length	112"
Weight	1550 lbs. (desiccant only) 1675 lbs. (desiccant with frame)

#### Accessories

4029522	Flex Duct 18"x25'
4029256	Lay Flat Duct 18" Round x 250'
4029257	Lay Flat Duct 20" Round x 250'
4029523	Flex Duct 20"x25'

### PowerDry 4800D Pro P (Propane) Specifications

<b>Part No.</b>	4028204 (with Frame) 4029194 (without Frame)
<b>Power</b>	240V single-phase unit, 70 amps
<b>Water</b>	3032 pints/day @ AHAM
<b>Removal</b>	(379 Gallons)
<b>Blower</b>	4800 CFM Process Air
<b>Operating Range</b>	-10°F to 140°F
<b>Duct Options</b>	18" to 20" Flex Duct and Lay Flat
<b>Warranty</b>	2 years; 1st year Parts and Service 2nd year Silica Gel Rotor

#### Dimensions

Width	48"
Height	56"
Length	112"
Weight	1550 lbs. (desiccant only) 1675 lbs. (desiccant with frame)



Quest Dry DDS 375e  
(Electric with and  
without frame)

#### Features:

- 3032 pints/day AHAM (379 Gallons)
- 4800 CFM process airflow
- Dries in temperatures to 140°F
- Reaches dew points as low as -40°F
- 48"W x 112"L x 56"H
- 1550 lbs. (desiccant only)
- 1675 lbs. (desiccant with frame)

#### PowerDry 4800D Pro e

- 480 volt 3-phase
- 106 full load amps

#### PowerDry 4800D Pro p

- 240V single phase
- 70 amps
- Propane cylinder and trailer mount available



Engineered Excellence for  
Construction Professionals



Specifications subject to change without notice. 03/14



Therma-Stor<sup>llc</sup>  
4201 Lien Rd  
Madison, WI 53704

1-866-933-7486  
www.QuestProtect.com  
sales@QuestProtect.com