



Electric Heater

Power Electric Heat EHS 31 Pro Specifications

Part Number	4030220	
Power	220/240V, 50/60Hz, 1 Phase Heater Circuits Amp selection switch on unit; 30 or 50 amp operation using 240V is below: 30 Amp = 46°F temperature rise; 18,000 BTUs 50 Amp = 80°F temperature rise; 31,000 BTUs (Note: 50 Amp using 220V = 28,000BTUs)	
	Two 8' Power Cords (1 dryer, 1 range) included with unit	
	Quest Remote Thermostat (30°F-140°F Temperature Range) with 25' connecting wire included with unit	
Blower	360 CFM	
Filters	Pleated Media MERV-11	
Duct Options	Inlet – 12" Flex-Duct Outlet – 12" Flex-Duct	
Warranty	One year 100% of Parts and Labor	
Dimensions		
	Unit	Shipping
Width	20.25"	27.5"
Height	40"	45.25"
Depth	21.4"	25.5"
Weight	90 lb	115 lb

Popular Accessories And Replacement Filters

4024750	12" x 25' Intake Flex Duct
4024969	16" x 20" x 2" Pleated Media MERV-8
4021475	16" x 20" x 2" Standard Pleated Media MERV-11
4027326	25' 240V Cord Kit
4031045	50' 240V Cord Kit
4031046	75' 240V Cord Kit
4031047	100' 240V Cord Kit



Quest Power Electric Heat
EHS 31 Pro

ETL Listed



Intertek

Features:

- Listed by ETL to UL Safety Standards, NEC Compliant
- Startup Delay to prevent dangerous arcing/sparking
- Double-Walled, Screened Enclosure for heating elements
- Automatic Low-Airflow Shutoff
- Internal 140°F Safety Thermal Cutouts
- Two 8' 4-Pole Grounded Power Cords (1 dryer, 1 range) included with unit
- Quest Thermostat with 25' connecting wire included with unit
- Unique multiple ducting options
12" inlet, 12" outlet
- Detachable 12" Duct Collar stores in lid with room for power cords
- Stainless steel cabinet



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 03/17



Therma-Stor LLC
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com